iSupply software application - release advice - version 7.37.2.1

Prerequisites - iSupply
iSupply version 7.37.1.1
Microsoft .NET Framework 4.0
Microsoft Report Viewer 2010 SP1
SAP Crystal Reports Runtime Engine for .NET Framework 4

Prerequisites - iSupplyRF
Microsoft .NET Compact Framework 3.5

iSupply release and version details
iSupply version: 7.37.2.1
Release status: General release
Applications released: iSupply, iSupplyWeb, iSupplyRF

This release must be installed to the test environment and user acceptance tested before installation to the live environment

iSupply version 7.37.2.1   released 25/08/2009 (016021)
MSI path and name: http://www.lsi.net.au/files/versions/iSupply-7-37-2-1.zip
SQL update scripts: DB7-37-2-1.sql

Release inclusions and notes

Job-no	Code	Details/remarks
015647	LS	iSupplyWeb - Internet Explorer 8 compliance
015863	LS	Import orders - EDIPlus and Integrator - rectify program crash if advertise date is in an incorrect format
015907	HW	Setup scheduled tasks - rectify truncated export directory path in add/change mode
015929	HW	Import pick slips - update help to include text file import in MAS727P format
015970	UT	Export consignment data to transporter - add Bluestar Logistics revised format
016043	IG	Import orders - EDIPlus and Integrator - adjust blanket and release order processing
016044	DH	Consignment details entry - rectify freight charge not being generated for swap-out consignments
016067	DH	Freight movements maintenance - rectify leg service delete misoperation
016076	HW	Confirmed pick slip export - Prism - adjust the trigger for export timing during consignment creation
016098	MS	Consignment details entry/update/enquiry - Toll Priority 150mm X 100mm label - remove erroneous leading space from barcode
016113	DH	Consignment details entry/update/enquiry - Toll Priority label - rectify incorrect sender address details on swap-out consignments

New maintainable settings

Setting	Details
None	None

Import/export file format changes

Transaction	Data fields
Carrier Export - Toll Priority	- Correct length of header record - Correct length of connote shipment flag - Correct output of sender name - Correct length of tail record

Notes

Trading partner details maintenance
==============================
The "Logistics label printer" setting set to "Blaster" with the "Retailer" setting set to "Generic" will print an SSCC label similar to the Coles Group/Myer format. This is in line with the "Logistics label printer" setting set to "Zebra" with the "Retailer" setting set to "Generic", which currently prints an SSCC label similar to the Coles Group/Myer format.

iSupply install steps for this release when upgrading from iSupply version 7.37.1.1

Preparation

1. Ensure all users are logged out of iSupply and cannot log in.
2. Stop the eCS service on the server that runs it.
3. Stop any external processes that may access the iSupply database.
4. Make a backup copy of the iSupply SQL database.

Application server (x86)

1. Uninstall the currently installed iSupply Windows version via Control Panel.
2. Uninstall the currently installed iSupply eCS Service version via Control Panel.
3. Install iSupply Windows 7-37-2-1.msi by running "setup.exe".
4. Ensure that the configuration file "C:\Program Files\LSI\iSupply Windows\iSupplyWindows.exe.config" has been updated with the server and database names.
5. Install iSupply eCS Service 7-37-2-1.msi by running "setup.exe".
6. Ensure that the configuration file "C:\Program Files\LSI\iSupply eCS Service \iSupplyeCSService.exe.config" has been updated with the server and database names.

Application server (x64)

1. Uninstall the currently installed iSupply Windows version via Control Panel.
2. Uninstall the currently installed iSupply eCS Service version via Control Panel.
3. Install iSupply Windows 7-37-2-1 x64.msi by running "setup.exe".
4. Ensure that the configuration file "C:\Program Files\LSI\iSupply Windows\iSupplyWindows.exe.config" has been updated with the server and database names.
5. Install iSupply eCS Service 7-37-2-1 x64.msi by running "setup.exe".
6. Ensure that the configuration file "C:\Program Files\LSI\iSupply eCS Service \iSupplyeCSService.exe.config" has been updated with the server and database names.
7. NGEN iSupply Windows
   7.1. Place the files "ngen.exe" and "NGENiSupplyWindows.bat" into iSupply's installation directory
   (Default: "C:\Program Files\LSI\iSupply Windows\Client\").
   7.2. Run the NGENiSupplyWindows.bat from command prompt as an Administrator
8. NGEN iSupply eCS Service
   8.1. Place the files "ngen.exe" and "NGENiSupplyeCSService.bat" into iSupply's installation directory
(Default: "C:\Program Files\LSI\iSupply eCS Service\Client\").
   8.2. Run the "NGENiSupplyeCSService.bat" from command prompt as an Administrator

Web server (x86)

1. Uninstall the currently installed iSupply Web Services version via Control Panel.
2. Uninstall the currently installed iSupply Web version via Control Panel.
3. Install iSupply Web Services 7-37-2-1.msi by running "setup.exe".
4. Ensure that the configuration file "C:\inetpub\wwwroot\iSupplyWebServices\Web.config" has been updated with the server and database names.
5. Install iSupply Web 7-37-2-1.msi by running "setup.exe".
6. Ensure that the configuration file "C:\inetpub\wwwroot\iSupplyWeb\Web.config" has been updated with the URL of the iSupplyWebServices.

Web server (x64)

1. Uninstall the currently installed iSupply Web Services version via Control Panel.
2. Uninstall the currently installed iSupply Web version via Control Panel.
3. Install iSupply Web Services 7-37-2-1 x64.msi by running "setup.exe".
4. Ensure that the configuration file "C:\inetpub\wwwroot\iSupplyWebServices\Web.config" has been updated with the server and database names.
5. Install iSupply Web 7-37-2-1 x64.msi by running "setup.exe".
6. Ensure that the configuration file "C:\inetpub\wwwroot\iSupplyWeb\Web.config" has been updated with the URL of the iSupplyWebServices.

Database server

1. Run the following database update script(s) (using SQL Server Management Studio) to update the iSupply database: DB7-37-2-1.sql.

Finalisation

1. Test run iSupply.
2. Start the eCS service on the server that runs it.
3. Start any external processes that may access the iSupply database.
4. Allow users to login to iSupply.